

Low Impact Development Checklist

A checklist for identifying nonstructural stormwater management strategies incorporated into proposed land development

Municipality: _____

County: _____ Date: _____

Review board or agency: _____

Proposed land development name: _____

Lot(s): _____ Block(s): _____

Project or application number: _____

Applicant's name: _____

Applicant's address: _____

Telephone: _____ Fax: _____

Email address: _____

Designer's name: _____

Designer's address: _____

Telephone: _____ Fax: _____

Email address: _____

Part 1: Description of Nonstructural Approach to Site Design

In narrative form, provide an overall description of the nonstructural stormwater management approach and strategies incorporated into the proposed site's design. Attach additional pages as necessary. Details of each nonstructural strategy are provided in Part 3 below.

Hartz Mountain Industries is proposing to redevelop and subdivide the subject site (Block 541, Lot 2 within the Township of Cranford, Union County) to accommodate two (2), 39,102 SF footprint, multi-family residential buildings and two (2) flex warehouses with 132,000 SF and 109,200 SF footprints, with the residential portion of the site taking up the southerly half of the property and the industrial use taking up the northerly half of the property. Additional site improvements include loading docks, parking, a park area in front of the residential buildings, stormwater management, landscaping, lighting, and utilities. Access to the site will be provide along three (3) driveways along Walnut Avenue, two for the residential use and one for the industrial use.

The project site is 30.8 acres, the extent of land disturbance is 28.9 acres, and the project will result in a reduction of 96,790 SF of impervious surfaces.

There are no environmentally sensitive areas on the project site and the site is not located within any flood zone. There are two existing stormwater management basins and an existing landscaping berm along the site frontage along Walnut Avenue.

The areas outside of the immediate buildings and park area will be planted with low maintenance native plantings.

Part 2: Review of Local Stormwater Management Regulations

Title and date of stormwater management regulations used in development design:

Do regulations include nonstructural requirements? Yes: _____ No: _____

If yes, briefly describe: _____

List LID-BMPs prohibited by local regulations: _____

Pre-design meeting held? Yes: _____ Date: _____ No: _____

Meeting held with: _____

Pre-design site walk held? Yes: _____ Date: _____ No: _____

Site walk held with: _____

Other agencies with stormwater review jurisdiction:

Name: _____

Required approval: _____

Name: _____

Required approval: _____

Name: _____

Required approval: _____

Part 3: Nonstructural Strategies and LID-BMPs in Design

3.1 Vegetation and Landscaping

Effective management of both existing and proposed site vegetation can reduce a development's adverse impacts on groundwater recharges and runoff quality and quantity. This section of the checklist helps identify the vegetation and landscaping strategies and nonstructural LID-BMPs that have been incorporated into the proposed development's design to help maintain existing recharge rates and/or minimize or prevent increases in runoff quantity and pollutant loading.

A. Has an inventory of existing site vegetation been performed? Yes: _____ No: _____

If yes, was this inventory a factor in the site's layout and design? Yes: _____ No: _____

B. Does the site design utilize any of the following nonstructural LID-BMPs?

Preservation of natural areas? Yes: _____ No: _____ If yes, specify % of site: _____

Native ground cover? Yes: _____ No: _____ If yes, specify % of site: _____

Vegetated buffers? Yes: _____ No: _____ If yes, specify % of site: _____

C. Do the land development regulations require these nonstructural LID-BMPs?

Preservation of natural areas? Yes: _____ No: _____ If yes, specify % of site: _____

Native ground cover? Yes: _____ No: _____ If yes, specify % of site: _____

Vegetated buffers? Yes: _____ No: _____ If yes, specify % of site: _____

D. If vegetated filter strips or buffers are utilized, specify their functions:

Reduce runoff volume increases through lower runoff coefficient: Yes: _____ No: _____

Reduce runoff pollutant loads through runoff treatment: Yes: _____ No: _____

Maintain groundwater recharge by preserving natural areas: Yes: _____ No: _____

3.2 Minimize Land Disturbance

Minimizing land disturbance is a nonstructural LID-BMP that can be applied during both the development's construction and post-construction phases. This section of the checklist helps identify those land disturbance strategies and nonstructural LID-BMPs that have been incorporated into the proposed development's design to minimize land disturbance and the resultant change in the site's hydrologic character.

A. Have inventories of existing site soils and slopes been performed? Yes: _____ No: _____

If yes, were these inventories factors in the site's layout and design? Yes: _____ No: _____

B. Does the development's design utilize any of the following nonstructural LID-BMPs?

Restrict permanent site disturbance by land owners? Yes: _____ No: _____

If yes, how: _____

Restrict temporary site disturbance during construction? Yes: _____ No: _____

If yes, how: _____

Consider soils and slopes in selecting disturbance limits? Yes: _____ No: _____

If yes, how: _____

C. Specify percentage of site to be cleared: _____ Regraded: _____

D. Specify percentage of cleared areas done so for buildings: _____

For driveways and parking: _____ For roadways: _____

E. What design criteria and/or site changes would be required to reduce the percentages in C and D above?

F. Specify site's hydrologic soil group (HSG) percentages:

HSG A: _____ HSG B: _____ HSG C: _____ HSG D: _____

G. Specify percentage of each HSG that will be permanently disturbed:

HSG A: _____ HSG B: _____ HSG C: _____ HSG D: _____

H. Locating site disturbance within areas with less permeable soils (HSG C and D) and minimizing disturbance within areas with greater permeable soils (HSG A and B) can help maintain groundwater recharge rates and reduce runoff volume increases. In light of the HSG percentages in F and G above, what other practical measures if any can be taken to achieve this?

I. Does the site include Karst topography? Yes: _____ No: _____

If yes, discuss measures taken to limit Karst impacts:

3.3 Impervious Area Management

New impervious surfaces at a development site can have the greatest adverse effect on groundwater recharge and stormwater quality and quantity. This section of the checklist helps identify those nonstructural strategies and LID-BMPs that have been incorporated into a proposed development's design to comprehensively manage the extent and impacts of new impervious surfaces.

A. Specify impervious cover at site: Existing: _____ Proposed: _____

B. Specify maximum site impervious coverage allowed by regulations: _____

C. Compare proposed street cartway widths with those required by regulations:

Type of Street	Proposed Cartway Width (feet)	Required Cartway Width (feet)
Residential access – low intensity		
Residential access – medium intensity		
Residential access – high intensity with parking		
Residential access – high intensity without parking		
Neighborhood		
Minor collector – low intensity without parking		
Minor collector – with one parking lane		
Minor collector – with two parking lanes		
Minor collector – without parking		
Major collector		

D. Compare proposed parking space dimensions with those required by regulations:

Proposed: _____ Regulations: _____

E. Compare proposed number of parking spaces with those required by regulations:

Proposed: _____ Regulations: _____

F. Specify percentage of total site impervious cover created by buildings:

By driveways and parking: _____ By roadways: _____

G. What design criteria and/or site changes would be required to reduce the percentages in F above?

H. Specify percentage of total impervious area that will be unconnected:

Total site: _____ Buildings: _____ Driveways and parking: _____ Roads: _____

I. Specify percentage of total impervious area that will be porous:

Total site: _____ Buildings: _____ Driveways and parking: _____ Roads: _____

J. Specify percentage of total building roof area that will be vegetated: _____

K. Specify percentage of total parking area located beneath buildings: _____

L. Specify percentage of total parking located within multi-level parking deck: _____

3.4 Time of Concentration Modifications

Decreasing a site's time of concentration (Tc) can lead directly to increased site runoff rates which, in turn, can create new and/or aggravate existing erosion and flooding problems downstream. This section of the checklist helps identify those nonstructural strategies and LID-BMPs that have been incorporated into the proposed development's design to effectively minimize such Tc decreases.

When reviewing Tc modification strategies, it is important to remember that a drainage area's Tc should reflect the general conditions throughout the area. As a result, Tc modifications must generally be applied throughout a drainage area, not just along a specific Tc route.

A. Specify percentage of site's total stormwater conveyance system length that will be:

Storm sewer: _____ Vegetated swale: _____ Natural channel: _____

Stormwater management facility: _____ Other: _____

Note: the total length of the stormwater conveyance system should be measured from the site's downstream property line to the downstream limit of sheet flow at the system's headwaters.

B. What design criteria and/or site changes would be required to reduce the storm sewer percentages and increase the vegetated swale and natural channel percentages in A above?

C. In conveyance system subareas that have overland or sheet flow over impervious surfaces or turf grass, what practical and effective site changes can be made to:

Decrease overland flow slope: _____

Increase overland flow roughness: _____

3.5 Preventative Source Controls

The most effective way to address water quality concerns is by pollution prevention. This section of the checklist helps identify those nonstructural strategies and LID-BMPs that have been incorporated into the proposed development's design to reduce the exposure of pollutants to prevent their release into the stormwater runoff.

A. Trash Receptacles

Specify the number of trash receptacles provided: _____

Specify the spacing between the trash receptacles: _____

Compare trash receptacles proposed with those required by regulations:

Proposed: _____ Regulations: _____

B. Pet Waste Stations

Specify the number of pet waste stations provided: _____

Specify the spacing between the pet waste stations: _____

Compare pet waste stations proposed with those required by regulations:

Proposed: _____ Regulations: _____

C. Inlets, Trash Racks, and Other Devices that Prevent Discharge of Large Trash and Debris

Specify percentage of total inlets that comply with the NJPDES storm drain inlet criteria: _____

D. Maintenance

Specify the frequency of the following maintenance activities:

Street sweeping: Proposed: _____ Regulations: _____

Litter collection: Proposed: _____ Regulations: _____

Identify other stormwater management measures on the site that prevent discharge of large trash and debris:

E. Prevention and Containment of Spills

Identify locations where pollutants are located on the site, and the features that prevent these pollutants from being exposed to stormwater runoff:

Pollutant: _____ Location: _____

Feature utilized to prevent pollutant exposure, harmful accumulation, or contain spills:

Pollutant: _____ Location: _____

Feature utilized to prevent pollutant exposure, harmful accumulation, or contain spills:

Pollutant: _____ Location: _____

Feature utilized to prevent pollutant exposure, harmful accumulation, or contain spills:

Pollutant: _____ Location: _____

Feature utilized to prevent pollutant exposure, harmful accumulation, or contain spills:

Pollutant: _____ Location: _____

Part 4: Compliance with Nonstructural Requirements of NJDEP Stormwater Management Rules

1. Based upon the checklist responses above, indicate which nonstructural strategies have been incorporated into the proposed development's design in accordance with N.J.A.C. 7:8-5.3(b):

No.	Nonstructural Strategy	Yes	No
1.	Protect areas that provide water quality benefits or areas particularly susceptible to erosion and sediment loss.		
2.	Minimize impervious surfaces and break up or disconnect the flow of runoff over impervious surfaces.		
3.	Maximize the protection of natural drainage features and vegetation.		
4.	Minimize the decrease in the pre-construction time of concentration.		
5.	Minimize land disturbance including clearing and grading.		
6.	Minimize soil compaction.		
7.	Provide low maintenance landscaping that encourages retention and planting of native vegetation and minimizes the use of lawns, fertilizers, and pesticides.		
8.	Provide vegetated open-channel conveyance systems discharge into and through stable vegetated areas.		
9.	Provide preventative source controls.		

2. For those strategies that have not been incorporated into the proposed development's design, provide engineering, environmental, and/or safety reasons. Attached additional pages as necessary.
